



SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM



Page: 1
Compilation date: 6/2/14
Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FILL AND FIX EXPANDING FOAM
Product code: EVFF5/7

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND

Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Email: pault@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/22; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20; N: R51/53; -: R64
Classification under CLP: STOT RE 2: H373; Aquatic Chronic 2: H411; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Aerosol 2: H223; Lact.: H362; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 2: H371; -: EUH204
Most important adverse effects: Highly flammable. Harmful by inhalation and if swallowed. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies.

2.2. Label elements

Label elements under CLP:

Hazard statements: H223: Flammable aerosol.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 2

Signal words: Danger
Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Precautionary statements:P102: Keep out of reach of children.
P211: Do not spray on an open flame or other ignition source.
P251: Pressurized container: Do not pierce or burn, even after use.
P260: Do not breathe.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Label elements under CHIP:

Hazard symbols: Flammable.
Dangerous for the environment.
Harmful.



Risk phrases: R11: Highly flammable.
R20/22: Harmful by inhalation and if swallowed.
R36/37/38: Irritating to eyes, respiratory system and skin.
R40: Limited evidence of a carcinogenic effect.
R42/43: May cause sensitisation by inhalation and skin contact.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R64: May cause harm to breastfed babies.

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 3

Safety phrases: S2: Keep out of the reach of children.
 S29: Do not empty into drains.
 S36/37: Wear suitable protective clothing and gloves.
 S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 S51: Use only in well-ventilated areas.
 S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
 S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Other hazards: In use, may form flammable/explosive vapour-air mixture.
PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.1. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

EINECS	CAS	CHIP Classification	CLP Classification	Per cent
-	9016-87-9	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE2: H371; STOT RE 2: H373	30-50%

TRI(2-CHLORISOPROPYL)-PHOSPHATE

-	13674-84-5	Xn: R22	-	10-30%
---	------------	---------	---	--------

ALKANES, C14-17, CHLORO

287-477-0	85535-85-9	-: R64; -: R66; N: R50/53	53 Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	10-30%
-----------	------------	---------------------------	--	--------

PROPANE

200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	---	-------------------------------------	-------

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 4

BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

ISOBUTANE

200-857-2	200-857-2	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	-----------	---	-------------------------------------	-------

DIMETHYL ETHER

204-065-8	115-10-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor. Remove/soften cured foam from skin with petroleum jelly or via constant softening with hot soapy water
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

- Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

- Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 5

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Do not use equipment in clean-up procedure which may produce sparks. Allow product to solidify and remove it by mechanical means. Remove uncured foam with acetone Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 6

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m ³	0.07 mg/m ³	-	-

PROPANE

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m ³	7200 mg/m ³	-	-

BUTANE

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m ³	1810 mg/m ³	-	-

ISOBUTANE

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2400 mg/m ³	9600 mg/m ³	-	-

DIMETHYL ETHER

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m ³	958 mg/m ³	-	-

8.1. DNEL/PNEC Values

DNEL/PNEC: No data available.

8.2. Exposure controls

- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor Self-contained breathing apparatus must be available in case of emergency.
- Hand protection:** Impermeable gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State:** Aerosol
- Colour:** Yellow
- Odour:** Barely perceptible odour
- Solubility in water:** Insoluble
- Viscosity:** Highly viscous
- Flammability limits %: lower:** 1.5 **upper:** 11
- Flash point°C:** 0

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of hydrogen cyanide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL	RAT	LD50	49	gm/kg
SKN	RBT	LD50	>9400	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH ING	Hazardous: calculated
Irritation	OPT INH DRM	Hazardous: calculated
Sensitisation	INH DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

Symptoms/routes of exposure

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 8

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: VOC 20% w/w

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Not dangerous to ozone layer (1999/45/EC)
Very toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J L47 of 16/2/2002): 08 05 01 (waste isocyanates)

Disposal of packaging: Waste material code packaging (91/689/EEC); Council decision 2001/118/EC, O.J L47 of 16/2/2001) 15 01 10 (packaging containing residues of or contaminated by dangerous substances)

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 9

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.
* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH204: Contains isocyanates. May produce an allergic reaction.
H220: Extremely flammable gas.
H223: Flammable aerosol.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335: May cause respiratory irritation.
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H362: May cause harm to breast-fed children.
H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
R11: Highly flammable.
R12: Extremely flammable.
R20/22: Harmful by inhalation and if swallowed.
R20: Harmful by inhalation.
R22: Harmful if swallowed.
R36/37/38: Irritating to eyes, respiratory system and skin.
R40: Limited evidence of a carcinogenic effect.
R42/43: May cause sensitisation by inhalation and skin contact.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

[cont...]

SAFETY DATA SHEET

FILL AND FIX EXPANDING FOAM

Page: 10

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R64: May cause harm to breastfed babies.

R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]